

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 091 374 A1

(12)

EUROPEAN PATENT APPLICATION

published in accordance with Art. 158(3) EPC

(43) Date of publication:

11.04.2001 Bulletin 2001/15

(51) Int. Cl.⁷: **H01H 13/14**, H01H 33/02

(21) Application number: 99926780.0

(86) International application number:

PCT/JP99/03357

(22) Date of filing: 24.06.1999

(87) International publication number:

WO 99/67799 (29.12.1999 Gazette 1999/52)

(84) Designated Contracting States:

CH DE ES FR LI

(72) Inventor:

TAMURA, Ken,

Omron Corporation

Shimogyo-ku, Kyoto-shi, Kyoto-fu 600-8530 (JP)

(30) Priority: 25.06.1998 JP 17837498

(71) Applicant: Omron Corporation

Kyoto-shi, Kyoto-fu, 600-8530 (JP)

(74) Representative:

Kilian, Helmut, Dr.

Wilhelms, Kilian & Partner

Patentanwälte


Eduard-Schmid-Strasse 2

81541 München (DE)

(54) SWITCH

(57) It is a principal object to provide a switch in which the space can be reduced and the cost can be lowered. It is another object to provide a switch of high reliability in which built-in components are not detached even when a shock is applied to the switch. A micro-switch 4 which is actuated by an operative plunger 2, and LEDs 14 are mounted on the same circuit board 5. It is configured so that light from the LEDs 14 is diffused and guided to an operation face 10a on the upper side by the operative plunger 2. A metal plate 12 is attached into the internal space of the operative plunger 2. According to this configuration, inward bending of the operative plunger 2 due to a shock or the like is prevented from occurring, and engagement between engaging holes 3b of a case 3 and engaging protrusions 2a of the operative plunger 2 is prevented from being cancelled.

Fig. 1



EP 1 091 374 A1

Description

Technical Field

[0001] The present invention relates to a switch 5 such as an illuminated push button switch.

Background Art

[0002] As a switch of this kind, for example, an illuminated push button switch, there is a switch that, as shown in Fig. 8, comprises: a switch circuit board 21 on which a microswitch 20 is mounted and which is disposed in a lower portion; and an illumination circuit board 23 on which an LED that is not shown is mounted, and which is disposed in an upper portion so as to be opposed to a glass plate 22 serving as an operation face. The circuit boards are connected to each other by a lead wire 24. When the glass plate 22 is pressed, an operative plunger 25 is downward displaced to turn on the microswitch 20 in the lower portion. This causes the LED that is not shown and that is in the upper portion, to emit light to illuminate the glass plate 22.

[0003] In the switch of the conventional art example, however, the switch circuit board 21 on which the microswitch 20 driven by the operative plunger 25 is mounted, and the illumination circuit board 23 for illuminating the operation face must be independently disposed in the lower and upper portions, respectively. Consequently, such a switch has problems in that an extra space is required, and that the cost is high.

[0004] In the push button switch, there is a case where the operation face is excessively pressed and operated. It is requested that internal built-in components are not detached even by a shock produced in such a case.

[0005] The invention has been conducted in view of these problems. It is a principal object of the invention to provide a switch in which the space can be reduced and the cost can be lowered. It is another object of the invention to provide a switch of high reliability in which built-in components are not detached even when a shock is applied to the switch.

Disclosure of Invention

[0006] In order to attain the objects, the invention is configured in the following manner.

[0007] The switch of the invention set forth in claim 1 is configured so that the switch comprises: an operating member which is displaced in accordance with an operation performed on an operation face; a switch main unit which actuates according to the displacement of the operating member; and a light source which operates according to the actuation of the switch main unit, the switch main unit and the light source are mounted on a same circuit board, and light from the light source is guided to the operation face by the operating mem-

ber.

[0008] According to the invention set forth in claim 1, light from the light source is guided to the operation face by the operating member, and hence the light source and the switch main unit can be mounted on the same circuit board. As compared with the conventional art example in which individual boards are disposed, therefore, the cost can be lowered and the space can be reduced. Since light is guided through the operating member which drives the switch main unit, furthermore, it is not required to separately dispose light guiding means.

[0009] The switch of the invention set forth in claim 2 is configured so that, in the invention set forth in claim 1, the operating member is displaceably built into the case with engaging an engaging portion of the operating member with an engagement receiving portion of the case, and a blocking member is disposed in an open internal space of the operating member, the blocking member abutting against an inner wall of the operating member and blocking the operating member from being inward bent, to hold the engagement state with the case.

[0010] According to the invention set forth in claim 2, the blocking member which blocks the operating member from being inward bent is disposed in the open internal space of the operating member which is displaceably built into the case. Even when a shock is applied by an excessive operation or the like, therefore, the operating member is not inward bent and the engagement state with the case on the outer side is not canceled. As a result, a switch of high reliability is obtained.

[0011] The switch of the invention set forth in claim 3 is configured so that, in the invention set forth in claim 1 or 2, the operating member is displaceably built into the case with engaging an engaging portion of the operating member with an engagement receiving portion of the case, a base on which the circuit board is mounted is coupled to the case, and a blocking portion which protrudes from the base is positioned in an open internal space of the operating member, to abut against an inner wall of the operating member, whereby the operating member is blocked from being inward bent, to hold the engagement state with the case.

[0012] According to the invention set forth in claim 3, in order to block the operating member from being inward bent, the blocking portion which protrudes from the base is positioned in the open internal space of the operating member which is displaceably built into the case. As a result, even when a shock is applied by an excessive operation or the like, the operating member is not inward bent, the engagement state with the case on the outer side is not canceled, and a switch of high reliability is obtained.

[0013] The switch of the invention set forth in claim 4 is configured so that, in the invention set forth in claim 2, an engaging hole is formed in the case, an engaging

protrusion which is to be engaged with the engaging hole is formed on the operating member, a pair of holding grooves which hold ends of the plate-like blocking member are formed in the inner wall of the operating member, and an engagingly locking protrusion which is to be engagingly locked with an engaging hole formed in the blocking member protrudes from the inner wall of the operating member.

[0014] According to the invention set forth in claim 4, the plate-like blocking member is surely held by the holding grooves and the engagingly locking protrusion which are formed in the inner wall of the operating member. Therefore, the operating member can be more surely prevented from dropping off from the case.

[0015] The switch of the invention set forth in claim 5 is configured so that, in the invention set forth in claims 1 to 4, the operating member is formed into a bottomed cylindrical shape, and built so that a bottom is positioned in an upper portion of the cylindrical case and an open end is positioned in a lower portion of the cylindrical case, slits are formed in a peripheral wall of the operating member on a side of the open end, to branch the operating member into plural portions, a base on which the circuit board is mounted is fittingly coupled to the case from a lower end opening of the case, and the switch main unit mounted on the circuit board is positioned in an internal space of the operating member from the open end of the operating member.

[0016] According to the invention set forth in claim 5, slits are formed in the peripheral wall of the operating member on the side of the open end, to branch the operating member into plural portions. During a process of incorporating the operating member into the cylindrical case, therefore, the branched peripheral wall of the operating member is inward bent, so that the incorporation can be smoothly conducted. There is a further effect that the open internal space of the operating member can be effectively used as a space for disposing the switch main unit.

Brief Description of Drawings

[0017]

Fig. 1 is an external perspective view of the whole of a push button switch according to the invention.
Fig. 2 is an exploded perspective view of the whole of the switch.

Fig. 3 is a vertical section side view of Fig. 1.

Fig. 4 is a vertical section side view of Fig. 1.

Fig. 5 is a vertical section side view of Fig. 1.

Fig. 6 is a vertical section side view of Fig. 1.

Fig. 7 is a plan view of an operative plunger of Fig. 1.

Fig. 8 is a section view of a conventional art example.

Best Mode for Carrying Out the Invention

[0018] Hereinafter, an embodiment of the invention will be described with reference to the drawings. Fig. 1 is an external perspective view of an illuminated push button switch to which the invention is applied, Fig. 2 is an exploded perspective view of the switch, and Figs. 3 to 6 are vertical section views of the switch.

[0019] The push button switch 1 is applied to, for example, a push button switch for an elevator. A case 3 and a base 6 are fittingly coupled to each other so as to be separable as described later. An operative plunger 2 serving as the operating member, and the like are housed in the case 3. A microswitch 4 serving as the switch main unit, a circuit board 5, and the like are mounted on the base 6.

[0020] The case 3 is a resin molded product which is substantially cylindrical. A flange 7 is attached to an upper edge of the case, and the operative plunger 2 and the like are built into the case as described later. A thread portion 3a is formed on the case 3. An attaching ring 8 is screwed and fastened to the thread portion to attach the case 3 to an attachment hole of an operation panel which is not shown.

[0021] Rectangular engaging holes 3b for enabling the operative plunger 2 to be built so as to be operatively displaceable in vertical directions are formed in four positions in the circumferential direction of the case 3, respectively. On the other hand, in the operative plunger 2 which is made of a transparent resin material, engaging protrusions 2a which are to be engaged with the engaging holes 3b are formed in four positions of the outer periphery, respectively. The engaging protrusions 2a are displaceably engaged with the engaging holes 3b of the case 3, whereby the operative plunger 2 is built into the case 3 so as to be operatively displaceable.

[0022] A pair of opposing legs 3c downward elongate from a lower portion of the case 3 in a cantilevered manner. On the other hand, a pair of opposing legs 6a which correspond to the legs 3c of the case 3 elongate from a lower portion of the resin base 6 having a substantially disk-like shape. Engaging holes 3d are formed in the legs 3c of the case 3, respectively. By contrast, engaging protrusions 6b which are to be engaged with the engaging holes 3d are formed on the legs 6a of the base 6, respectively. When the operative plunger 2 and the like are attached into the case 3 and the above-mentioned legs 3c and 6a are then engaged with each other, therefore, the case 3 and the base 6 are fittingly coupled to each other in a state where they are relatively positioned.

[0023] The operative plunger 2 is formed into a bottomed cylindrical shape. A peripheral wall of the plunger on the side of the lower open end is branched into plural portions by forming a slit 2b elongating in the longitudinal direction, in plural positions arranged along the circumferential direction, in order that, when the operative

plunger 2 is to be inserted into the cylindrical case 3 to be built thereinto, the peripheral wall is inward bent to allow the insertion to be smoothly conducted. The engaging protrusions 2a are formed on the outer peripheries of four opposing ones of the branched portions, respectively.

[0024] A display plate 9 and a glass plate 10 constituting the operation face, are placed on the upper end face of the operative plunger 2, and built into the case 3 under the placed state. The lower portion of the operative plunger 2 is opened, and an internal space for housing the microswitch 4 and the like is configured inside the plunger. In the internal space, as shown Fig. 3, a pressing portion 2c which presses a lever 4a of the microswitch 4 downward protrudes from the inner wall of the upper portion. As shown in Fig. 4, in order to attach a pair of springs 11 for urging in the returning direction, a pair of attaching protrusions 2d downward protrude from the operative plunger 2. As shown in Fig. 5, a pair of holding grooves 2e which guide and hold a plate 12 that serves as the blocking member and that will be described later are formed in the vertical direction in inner walls of a pair of branched portions on which the engaging protrusions 2a are formed. A hook 2f serving as an engaging protrusion for preventing the plate 12 from slipping off protrudes downward from the inner wall of the upper portion.

[0025] When the engaging protrusions 2a formed on the outer peripheries of the four branched portions of the plunger are respectively engaged with the engaging holes 3b formed in the four positions in the circumferential direction of the case 3 with a so-called snap fit, therefore, the operative plunger 2 is built so as to be operatively displaceable. In the embodiment, the pair of branched portions on which the engaging protrusions 2a of the operative plunger 2 are formed are blocked from being inward bent, by attaching the metal plate 12 into the internal space of the operative plunger 2. This configuration is employed in order to prevent the phenomenon in which the engaging portions wherein engagement is attained with a snap fit are disengaged by a shock due to an excessive pressing operation on the operation face 10a or the like and the operative plunger 2 slips off from the case 3, from occurring.

[0026] The plate 12 has a pair of abutting portions 12a which opposingly elongate, and a connecting portion 12b through which the abutting portions 12a are connected to each other, and is formed into a substantially U-like shape. In order to prevent the plate 12 from escaping from the internal space of the operative plunger 2, an engagingly locking hole 12c which is to be engagingly locked with the hook 2f that protrudes inside the operative plunger 2 is formed in the connecting portion 12b.

[0027] After the operative plunger 2 is displaceably built into the case 3, as shown in a plan view (Fig. 7) as seen from the lower side of the operative plunger 2, the abutting portions 12a of the plate 12 are inserted from

the lower side into the holding grooves 2e formed in the inner walls of the pair of opposing branched portions of the operative plunger 2, respectively. Thereafter, the engagingly locking hole 12c of the connecting portion 12b is engagingly locked with the hook 2f of the operative plunger 2 to attain attachment.

[0028] As a result, the positions of the branched portions on which the engaging protrusions 2a of the operative plunger 2 are formed are restricted by the plate 12, and the branched portions are not therefore inward bent. Consequently, the engagement between the engaging protrusions 2a which are respectively disposed on the pair of opposing branched portions of the operative plunger 2, and the engaging holes 3b of the case 3 can be effectively prevented from being canceled.

[0029] In the embodiment, the microswitch 4 which is driven by displacement of the operative plunger 2, and a resistor 13 are mounted on the disk-like circuit board 5. On the circuit board 5, moreover, plural LEDs 14 which are light sources for illuminating the edge of the operation face 10a, i.e., the periphery of the display plate 9, are mounted along the circumferential direction, and a connector 15 is mounted via the base 6. Through holes 5a through which projections of the base 6 are to be passed are formed in the circuit board 5.

[0030] The LEDs 14 are arranged so as to be opposed to the lower end of the peripheral wall of the operative plunger 2. Therefore, light of the LEDs 14 is diffusedly guided through the operative plunger 2 to the operation face 10a on the upper side. Since light of the LEDs 14 is guided by the operative plunger 2 to the operation face 10a on the upper side in this way, the LEDs 14 and the microswitch 4 which is placed in the lower portion can be mounted on the same circuit board 5. Unlike the above-described conventional art example, therefore, it is not required to separately dispose a switch circuit board and an illumination circuit board. As a result, the cost can be lowered, and the space can be reduced. Since light is guided to the operation face 10a through the operative plunger 2 which drives the microswitch 4, moreover, it is not required to separately dispose light guiding means.

[0031] Through holes 6c and 6d through which lead terminals 4b of the microswitch 4 and terminals 15a of the connector 15 which are mounted on the circuit board 5 can be passed are formed in the resin base 6. A supporting column 6e which supports a basal end portion of the lever 4a of the microswitch 4 upstands from the base 6. Receiving portions 6f which respectively receive the springs 11 for urging the operative plunger 2 in the returning direction protrude from the base 6 so as to be opposed to each other. As shown in Fig. 6, a pair of locking protrusions 6g protrude from the base 6 so as to be opposed to each other. This configuration is employed in order to block the pair of branched portions on which the engaging protrusions 2a of the operative plunger 2 are formed, from being inward bent,

and prevent the engagement between the case 3 and the operative plunger 2 from being canceled.

[0032] In the embodiment, namely, among the four branched portions on which the engaging protrusions 2a of the operative plunger 2 are formed, the pair of opposing branched portions are blocked from being inward bent, by the plate 12 which is attached to the inside of the operative plunger 2. On the other hand, the positions of the pair of branched portions on which the engaging protrusions 2a are formed in a direction perpendicular to the plate 12 are restricted by the locking protrusions 6g of the base 6, to be blocked from being inward bent. According to this configuration, the engagement between the case 3 and the operative plunger 2 which is built into the case 3 is not caused by a shock or the like to be canceled, and the operative plunger 2 can be surely prevented from dropping off from the case.

[0033] In the thus configured push button switch 1, when the operation face 10a is pressed, the operative plunger 2 is downward displaced against the urging force of the spring 11. The pressing portion 2c which is placed inside the switch 1 presses the lever 4a of the microswitch 4 to drive the microswitch 4. As a result, the LEDs 14 emit light, and the light is diffused and guided via the operative plunger 2 to the operation face 10a on the upper side, to illuminate the edge of the display plate 9.

[0034] In the embodiment, as shown in Fig. 3, the pressing portion 2c of the operative plunger 2 presses the basal end side of the lever 4a of the microswitch 4 to operate an operating portion 4c on the side of the free end. Therefore, the microswitch 4 can be driven by a small operation stroke of the operation face 10a.

[0035] In the embodiment, the engagement between the case 3 and the operative plunger 2 is prevented from being canceled, by both the plate 12 and the locking protrusions 6g protruding from the base 6. In another embodiment of the invention, the engagement may be prevented from being canceled, by only either of the two means. In the other embodiment, the shape, the number, and the like of the plate 12 and the locking protrusions 6g can be adequately selected.

[0036] In the embodiment, the plural LEDs 14 are arranged along the circumferential direction, and the edge of the operation face 10a is illuminated via the operative plunger 2. However, the invention is not restricted to this. In a further embodiment of the invention, the whole face of the operation face 10a may be illuminated.

[0037] In the embodiment, the engaging holes 3b are formed in the case 3, and the engaging protrusions 2a are formed on the operative plunger 2. In a further embodiment of the invention, engaging protrusions may be formed on the case, and engaging holes or engaging recesses may be formed in the operative plunger.

Industrial Applicability

[0038] The application of the present invention is not restricted to a push button switch for an elevator, and the invention may be applied to other illuminated push button switches.

Claims

1. A switch characterized in that said switch comprises: an operating member which is displaced in accordance with an operation performed on an operation face; a switch main unit which actuates according to the displacement of said operating member; and a light source which operates according to the actuation of said switch main unit, said switch main unit and said light source are mounted on a same circuit board, and light from said light source is guided to said operation face by said operating member.
2. A switch according to claim 1, wherein said operating member is displaceably built into said case with engaging an engaging portion of said operating member with an engagement receiving portion of said case, and a blocking member is disposed in an open internal space of said operating member, said blocking member abutting against an inner wall of said operating member and blocking said operating member from being inward bent, to hold the engagement state with said case.
3. A switch according to claim 1 or 2, wherein said operating member is displaceably built into said case with engaging an engaging portion of said operating member with an engagement receiving portion of said case, a base on which said circuit board is mounted is coupled to said case, and a blocking portion which protrudes from said base is positioned in an open internal space of the operating member, to abut against an inner wall of said operating member, whereby said operating member is blocked from being inward bent, to hold the engagement state with said case.
4. A switch according to claim 2, wherein an engaging hole is formed in said case, an engaging protrusion which is to be engaged with said engaging hole is formed on said operating member, a pair of holding grooves which hold ends of said plate-like blocking member are formed in said inner wall of said operating member, and an engagingly locking protrusion which is to be engagingly locked with an engaging hole formed in said blocking member protrudes from said inner wall of said operating member.
5. A switch according to any one of claims 1 to 4,

wherein said operating member is formed into a
bottomed cylindrical shape, and built so that a bot-
tom is positioned in an upper portion of said cylin-
drical case and an open end is positioned in a lower
portion of said cylindrical case, slits are formed in a
peripheral wall of said operating member on a side
of said open end, to branch said operating member
into plural portions, a base on which said circuit
board is mounted is fittingly coupled to said case
from a lower end opening of said case, and said
switch main unit mounted on said circuit board is
positioned in an internal space of said operating
member from said open end of said operating
member.

5

10

15

20

25

30

35

40

45

50

55

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig.5




Fig. 6




Fig. 7





Fig. 8



INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP99/03357

A. CLASSIFICATION OF SUBJECT MATTER

Int.Cl.¹ H01H13/14, H01H33/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

Int.Cl.¹ H01H13/14, H01H33/02

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Jitsuyo Shinan Koho 1926-1996 Toroku Jitsuyo Shinan Koho 1994-1999
 Kokai Jitsuyo Shinan Koho 1971-1999 Jitsuyo Shinan Toroku Koho 1996-1999

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	JP, 3-116622, U (DK Antenna Co., Ltd.), 12 March, 1991 (12. 03. 91), Figs. 1 to 4 (Family: none)	1 2-5
X	JP, 59-43023, U (Oki Electric Industry Co., Ltd.), 21 March, 1984 (21. 03. 84), Figs. 1, 2 (Family: none)	1 2-5
X	JP, 61-53829, U (Fujitsu Ten Ltd.), 11 April, 1983 (11. 04. 83), Figs. 1 to 4, 5, 6 to 8 (Family: none)	1 2-5
Y	JP, 4-92323, A (Alps Electric Co., Ltd.), 25 March, 1992 (25. 03. 92), Page 4, upper right column, lines 2 to 6 (Family: none)	2-5

☒ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:

"A" documents defining the general state of the art which is not considered to be of particular relevance

"B" earlier document but published on or after the international filing date
"C" document which may show doubt on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"D" document referring to an oral disclosure, use, exhibition or other means

"E" document published prior to the international filing date but later than the priority date claimed

"F" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is considered in combination with one or more other such documents, such combinations being obvious to a person skilled in the art

"A" document member of the same patent family

Date of the actual completion of the international search
9 September, 1999 (09. 09. 99)Date of mailing of the international search report
21 September, 1999 (21. 09. 99)Name and mailing address of the ISA/
Japanese Patent Office

Authorized officer

Facsimile No.

Telephone No.

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP99/03357

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	JP, 2550816, Y (Matsushita Electric Industrial Co., Ltd.), 15 October, 1997 (15. 10. 97), Column 3, lines 22 to 29 ; column 4, lines 21 to 28 (Family: none)	2-5
Y	JP, 3-7228, U (Kenwood Corp.), 24 January, 1991 (24. 01. 91), Claims ; Figs. 1 to 3 (Family: none)	2-5
Y	JP, 57-145228, U (Maspro Denkoh Corp.), 11 September, 1982 (11. 09. 82), Page 6, lines 7 to 13 (Family: none)	5

Form PCT/ISA/210 (continuation of second sheet) (July 1992)